

**Product Type:** QBV657<sup>EXP1D</sup>



1-800-773-0062  
www.marianinc.com

**Description:** Oleophobic ePTFE Membrane Laminate  
Functional Layer: PTFE  
Backer Material: Polyamide, yellow

Water Entry Pressure	≥ 14.5 psi (> 1.0 bar), ASTM D751
Air Permeability	500 mL/min/cm <sup>2</sup> @ 1 psi, ASTM D737
Oil Repellency Rate	8, AATCC 118
Thickness	Nom. 5 mil (0.13mm), ASTM D1777
Moisture Vapor Transmission Rate	>13,500 g/m <sup>2</sup> /day, JIS L1099 B-2
Available Dimensions	OEM Membranes: customs slit roll goods. Membrane vents: customized shapes

All above data is nominal and provided for information only and is subject to change.  
All metric conversions are approximate.



For more information, contact your GE representative  
or visit [www.ge-energy.com/membrane](http://www.ge-energy.com/membrane)

8800 East 63rd Street Kansas City, MO, 64133 USA  
P: 800.391.0686 / 816.356.5515 , F: 816.246.9592

Balsthalerstrasse 1, 4717 Muemliswil, Switzerland  
P: +41.62.386.7733, F: +41.62.386.7744

\* Trade Mark of General Electric Company  
© 2008 General Electric Company. All rights reserved.

GEA-1623 (2.26.08)