



Straight up versatile



Long, straight lines, sharp edges.

Think tough and think straight when you think Scotch® Ultimate Paint Edge Masking Tape 2460. This ultra-thin, ultra-smooth tape is ideal for creating the long, straight, smooth paint lines you need for the highest quality finished products. Yet it is strong enough to pull through paint and caulk without ripping. And it peels off clean with no adhesive residue, even when exposed to high temperatures (up to 300°F). It's the versatile gold tape that can handle many challenges.

Scotch® Ultimate Paint Edge Masking Tape 2460 provides:

- Distinctive gold color helps avoid “which tape to use” confusion and helps eliminate taping errors
- Resists elongation for true, straight paint lines
- Ultra thin for a virtually undetectable paint ridge
- Cross tears easily by hand
- Not affected by most solvents or latex paints


Scotch® Ultimate Paint Edge Masking Tape 2460



Creating long, straight paint lines is easy. ²



Ideal for paint bake operations. ³



⁴

Tape Size	Tape Structure (Backing/Adhesive)	Total Thickness Milis (mm)	Adhesion oz./in. (N/100mm)	Tensile Strength lbs./in. width (N/100mm)	Elongation at Break %	Temperature Range °F (up to)	UPC	Rolls/Case
1/2" x 60 yds.	Flatback paper/Acrylic	3.3 (0.08)	9 (9.8)	17 (299)	5%	300°F	00-051111-91672-8	72
3/4" x 60 yds.	Flatback paper/Acrylic	3.3 (0.08)	9 (9.8)	17 (299)	5%	300°F	00-051111-91927-9	48
1" x 60 yds.	Flatback paper/Acrylic	3.3 (0.08)	9 (9.8)	17 (299)	5%	300°F	00-051111-91928-6	36
1-1/2" x 60 yds.	Flatback paper/Acrylic	3.3 (0.08)	9 (9.8)	17 (299)	5%	300°F	00-051111-91929-3	24
2" x 60 yds.	Flatback paper/Acrylic	3.3 (0.08)	9 (9.8)	17 (299)	5%	300°F	00-051111-91930-4	24

TECHNICAL INFORMATION: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

WARRANTY, LIMITED REMEDY, AND DISCLAIMER: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships

the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

LIMITATION OF LIABILITY: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
1-800-362-3550
www.3M.com/colormaskingtapes
www.3M.com/industrialtapes

3M and the Plaid Design are trademarks of 3M Company. Scotch is a registered trademark of 3M Company. Please recycle. Printed in USA. © 2010, 2011, 3M. All rights reserved. 70-0711-0226-6 (Rev. A)



www.marianinc.com

1-800-773-0062